

Nourison
Specifications
Nepal Collection

Style Name.....	Butwal
Pile Weight (ASTM D 5848).....	52 oz/sq/yd
Total Weight (ASTM D 5848).....	97 oz/sq/yd
Construction.....	Wilton
Fiber.....	75.76% Wool 24.24% Viscose
Pile Height (ASTM D 418).....	393”
Total Height (ASTM D 418).....	472”
Count and Plies.....	Wool 9s/3 Viscose 13s/4
Dye Method.....	Space Dyed
Rows Length.....	32.51 stitches per inch
Pitch Width.....	8.25 stitches per inch
Width.....	13.12”
Backing.....	weft+warp+latex+pile yarn
Pattern repeat Width.....	6.65”
Pattern repeat Length.....	8.3”
Flammability (CPSC FF 1-70; 16CFR 1630; ASTM D 2859-96).....	pass
Smoke Density Test (NIST 708; NFPA 258; ASTM E 662-97).....	pass
Flooring Radiant Panel Test (ASTME 648-99); FTM 372; NFPA 253).....	pass

Nourison recommends that installation be completed by a CFI certified installer with at least a R2 certification or equivalent too.

Product specifications are derived from averages, allowing for normal manufacturing tolerances in yarn, fiber, temperature, humidity and color, and may vary within those normal industry tolerances. Product performance is not affected by these variances.

Chair pads are required under roller casters to preserve appearance, and prevent accelerated wear.

As is the case with all quality carpets, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible with seams running perpendicular to major (outside) lighting sources.

Shading is the result of pile distortion and often is described as water marking. Since this is an inherent characteristic of fine cut or loop pile carpet, shading does not constitute a manufacturing defect. Due to the special characteristics of “abrash” dyeing, striations are an inherent characteristic in this product. Shedding or “Fluffing” is a natural characteristic of all wool or wool blend pile carpets. Loose bits of staple fiber can appear and can be removed with gentle vacuuming. Improper maintenance, dragging objects, or overly-aggressive cleaning methods can distort pile and cause excessive fuzzing.

Installation should be done only by professional installers with specific expertise in fine broadloom carpet. This product is recommended for conventional tack and pad installation over a firm, dense pad.

This product from Nourison Industries Inc. is intended solely for the use as a floor covering and is not recommended or sold for any other purpose.

For more information, contact Nourison at 800-223-1110 or visit our website at www.nourison.com.

Except where noted as a minimum or maximum, the above specifications are nominal and, therefore, are subject to change and to normal manufacturing variance.