

Nourtex
Specifications
Point Pleasant Collection

Style name.....	Lattice
Pile Weight.....	36 oz. /yd. ²
Total Weight).....	84 oz. /yd. ²
Construction.....	Print Tufted Loop
Fiber	10%Wool/ 90%PET
Pile Height (ASTM D 418).....	.20”
Total Height (ASTM D 418).....	.28”
Gauge	1/4
Backing	Actionbac
Width.....	13.12
Flammability (CPSC FF 1-70; 16CFR 1630; ASTM D 2859-96).....	Pass
Smoke Density Test (NIST 708; NFPA 258; ASTM E 662-97)	Pass
Flooring Radiant Panel Test (ASTME 648-99); FTM 372; NFPA 253).....	Pass
Pattern Repeat	6.3” W x16.54” L
Application.....	Residential

Product specifications are derived from averages, allowing for normal manufacturing tolerances in yarn, fiber, temperature, humidity and color, and may vary within those normal industry tolerances. Product performance is not affected by these variances.

Chair pads are required under roller casters to preserve appearance, and prevent accelerated wear.

As is the case with all quality carpets, colors are subject to dye lot variations. For optimum side match and finished seam appearance, this product should be installed whenever possible with seams running perpendicular to major (outside) lighting sources.

Shading is the result of pile distortion and often is described as water marking. Since this is an inherent characteristic of fine cut or loop pile carpet, shading does not constitute a manufacturing defect. Due to the special characteristics of “abrash” dyeing, striations are an inherent characteristic in this product. Shedding or “Fluffing” is a natural characteristic of all wool or wool blend pile carpets. Loose bits of staple fiber can appear and can be removed with gentle vacuuming. Improper maintenance, dragging objects, or overly-aggressive cleaning methods can distort pile and cause excessive fuzzing.

Installation should be done only by professional installers with specific expertise in fine broadloom carpet. This product is recommended for conventional tack and pad installation over a firm, dense pad.

This product from Nourison Industries Inc. is intended solely for the use as a floor covering and is not recommended or sold for any other purpose.

For more information, contact Nourison at 800-223-1110 or visit our website at www.nourison.com.

Except where noted as a minimum or maximum, the above specifications are nominal and, therefore, are subject to change and to normal manufacturing variance.